

COB PRO SERIES



COB-24V-2700K- 549LM16FT



White Free-Cutting SMD

APPLICATION

Ideal for indirect lighting applied at contour, corridor, stair, cove, handrail, skirting, barrier, etc.



FEATURES

1. 24V system
2. Dimmable with dimmable power supply (MLV/ELV/TRIAC/0-10V Driver)
3. Delivering 549lm/4.6W per foot
4. Dedicated color temperatures (2700K, 3000K, 3500K, 4000K, 5000K or 6500K)
5. cULus listed for indoor dry location (IP20 rated)
6. Homogeneous and soft linear lighting performance for 5M[16.4ft.] length
7. Free-Cutting SMD strips are designed to offer a dotless Linear finish and be customised to precise lengths; feel free to cut anywhere along the LED Strips PCB board for a millimetre perfect finish.
8. Seamless COB eliminates LED dotting, ultra-thin appearance, and super flexible bending.
9. Easy installation with 3M™ adhesive pre-installed
10. Rolls include a 12" power cord
11. CRI90
12. Lifespan :50,000 hours

Model Number	COB-24V
CCT:	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
Wattage:	2700K-3500K-5.18W/FT 4000K-6500K-4.57W/FT
Lumen (/ft):	549
Length (ft):	16.4
Beam Angle:	120
Dimmable:	Yes

Operating Temperature:
Ta: -20~45°C [-4~113°F],
Tstog: -20~60°C [-4~140°F]




PICTURE & DIAGRAM




Unit: mm[in.]



ACCESSORIES & CONNECTORS




8 MM I Connector



8 MM L Connector



8 MM Power Feed



8 MM Jumper Power Feed